



ARMOPHALT GST

DESCRIPTION

GLASS GRID FOR ASPHALT REINFORCEMENT WITH TNT INCORPORATED

TYPE CHARACTERISTICS	NORM	UNIT	GST 50 DATA	GST100 DATA
WT	EN 9864	g/m ²	250(*)	450(*)
STRENGTH RESISTANCE LONG. SECTION	EN ISO 10319	kN/m	50	100
STRENGTH RESISTANCE CROSS SECTION	EN ISO 10319	kN/m	50	100
BREAKING ELONGATION LONG. SECTION	EN ISO 10319	%	2,5	2,5
BREAKING ELONGATION CROSS SECTION	EN ISO 10319	%	2,5	2,5
STRENGTH RESISTANCE LONG. SECTION AT 1,5% STRAIN	EN ISO 10319	kN/m	40	> 70
STRENGTH RESISTANCE LONG. SECTION AT 2 % STRAIN	EN ISO 10319	kN/m	45	> 80
TNT WT		g/m ²	13	15
NOMINAL MESH		mm	25x25	25x25
ROLL WIDTH		m	2.20	2.20
ROLL LENGTH		m	100	100

(*) Range of variation under factory quality control

G&P intech srl

Via Retrone, 39 - 36077 Altavilla Vicentina (VI)

Tel. 0444/522797 – Fax 0444/348692

C. F. e Partita IVA 03580250243 - Numero REA VI-0336685 - Capitale sociale € 100.000 i.v.

E-mail: info@gpintech.com - Sito internet: www.gpintech.com

Marchi registrati: Dual Seal® - FRP System® - Steel Net® - Armophalt® - Matacryn® - Superstop® - Concrete Rock® - Floor System® - GP Sunzenit® - Kryton® - Damp Stop® - Cemesan®